

KYNAR500FSF[®]
BY ARKEMA

Resin-based Metal Coatings for Residential Roofing



Photo courtesy of Classic Metal Roofing Systems

RESIN-BASED METAL COATINGS FOR RESIDENTIAL ROOFING

No Fading, No Chalking, No Chipping

Metal has rapidly become the material of choice for residential roofing. Architects are using it in new and bold ways. Metal is durable, saves energy, and is fire resistant, increases real estate value, and holds its beauty far longer than other roofing materials like composition or wooden shingles.

With all that said, metal must still be protected from weathering by a coating that will keep the appearance looking rich and vibrant year after year. And the premier metal finishes in all the world are those based on Kynar 500® PVDF resins.

Since 1965, Kynar 500® resin-based coatings have provided literally billions of square feet of protection against weathering, aging, and pollution on commercial, industrial, institutional, and residential buildings.

When compared to other metal coating technologies, Kynar 500® resin-based finishes clearly deliver exceptional performance. The panels shown at right, compiled by an independent testing laboratory, confirm Kynar 500® resin's superior performance over competing technologies.



Cool Metal Roofing Using KYNAR 500® FSF® Based Coatings

The choice of roofing material has the greatest impact on the energy efficiency of a home. Cool metal roofs coated with Kynar 500® resin-based coatings can reduce energy consumption by up to 40% as reported by the Oak Ridge National Laboratory as part of a total system design. Kynar 500® based painted metal roofing can achieve solar reflectance of over 70%. Reflected solar energy allows the roof surface to remain cooler, which means less heat is transferred into the building, resulting in lower home cooling costs.

Metal roofs coated with Kynar 500® resin-based paints are included on the U.S. EPA's Energy Star Roof Products Program as well as the California Energy Commission's Cool Roof Savings Program.

Metal roofing is tested for wind, fire and hail resistance and is listed within many building codes. Furthermore, tests performed by independent laboratories show Kynar 500® resin-based coatings possess exceptional flame retardant properties in addition to being extremely weatherable, durable and chemically resistant.



KYNAR 500® Resin vs. Competitors



15 Years Exposure

Unexposed | Exposed




17 Years Exposure

Unexposed | Exposed



17 Years Exposure

Unexposed | Exposed



17 Years Exposure

Unexposed | Exposed



Can you tell where the original leaves off and the addition picks up?

Weatherability Means Continuity

This house is located on the shores of Lake Erie in the United States, a region known for fierce winters. An addition was built five years after the initial construction. Obviously, the secret to building a successful addition is making it appear as if it were part of the original project. This can be a serious problem for painted metal unless the coating is based on Kynar 500® resin. Its capacity to retain a color's richness and luster—in the face of extreme weather and general wear and tear—allows you to confidently design additions without disrupting aesthetic continuity.



HOME DEPOT

The experts at Home Depot trust KYNAR 500® resin-based metal coatings to maintain consistent color year after year.

CONTACT US AROUND THE WORLD

Arkema Inc.
900 First Ave.
King of Prussia, PA 19406
800-KYNAR-500

Arkema
420 rue Estienne d'Orves
92705 Colombes Cedex France
(+33) (0) 1 49 00 80 80

Arkema
Ruby House, B Wing, 2nd Floor
J. K. Sawant Marg
Dadar (w), Mumbai 400 028 India
Tel: 91 22 2438 7500
Fax: 91 22 2438 7550

Arkema
Unit 2801-06, Hong Kong Plaza
283 Huai Hai Road (M)
Shanghai 200021, P.R. China
86-21-6386-3028

Arkema K.K.
Fukoku Seimei Bldg 15F
2-2-2 Uchisaiwaicho
Chiyoda-Ku
Tokyo 100-011, Japan
81-3-5251-9665

Arkema
11F, Oriental Chemical Building
50, Sogong-dong
Jung-gu, Seoul, 110-718, Korea
82-2-3703-6822

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, ARKEMA expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement. See SDS for Health & Safety Considerations. Arkema has implemented a Medical Policy regarding the use of Arkema products in Medical Devices applications that are in contact with the body or circulating bodily fluids: (<http://www.arkema.com/en/social-responsibility/responsible-product-management/medical-device-policy/index.html>).

Arkema has designated Medical grades to be used for such Medical Device applications. Products that have not been designated as Medical grades are not authorized by Arkema for use in Medical Device applications that are in contact with the body or circulating bodily fluids. In addition, Arkema strictly prohibits the use of any Arkema products in Medical Device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Arkema trademarks and the Arkema name shall not be used in conjunction with customers' medical devices, including without limitation, permanent or temporary implantable devices, and customers shall not represent to anyone else, that Arkema allows, endorses or permits the use of Arkema products in such medical devices. It is the sole responsibility of the manufacturer of the medical device to determine the suitability (including biocompatibility) of all raw materials, products and components, including any medical grade Arkema products, in order to ensure that the final end-use product is safe for its end use; performs or functions as intended; and complies with all applicable legal and regulatory requirements (FDA or other national drug agencies) It is the sole responsibility of the manufacturer of the medical device to conduct all necessary tests and inspections and to evaluate the medical device under actual end-use requirements and to adequately advise and warn purchasers, users, and/or learned intermediaries (such as physicians) of pertinent risks and fulfill any postmarket surveillance obligations. Any decision regarding the appropriateness of a particular Arkema material in a particular medical device should be based on the judgment of the manufacturer, seller, the competent authority, and the treating physician.

© 2015 Arkema Inc. All rights reserved.

Kynar®, Kynar 500® and FSF® are registered trademarks of Arkema Inc.

ARKEMA
INNOVATIVE CHEMISTRY

kynar500.com

Arkema Inc.
900 First Avenue
King of Prussia, PA 19406
USA
Tel.: (+1) 610-205-7000

Headquarters: Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex – France
Tel.: +33 (0)1 49 00 80 80
Fax: +33 (0)1 49 00 83 96
arkema.com